## **ALTERNATING TREAD STAIR - ATS-14-56** APPROX WEIGHT: 374.05 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\*ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE\*\*\* 23 5/8" 23 5/8" 20" 9 3/4" TOP STEP - SCALE: 1:12 210 3/8" 18 5/8' STEP - SCALE: 1:12 7" STEP **HEIGHT** 10 1/2" **SPACING** 166 1/2" 168" TOP STEP HEIGHT 27 1/2" 56° - 9 1/8" 117 5/8" 23 1/2" 122 3/8" ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON **STANDARD FEATURES** MODEL NUMBER: ATS-14-56

MODEL NUMBER: ATS-14-56
CLIMB ANGLE: 56°
NUMBER OF STEPS: 24
(INCLUDING TOP STEP)
TOP STEP HEIGHT: 168"
STEP HEIGHT SPACING: 7"
HANDRAIL HEIGHT: 18 5/8"
OVERALL HEIGHT: 210 3/8"
OVERALL LENGTH: 122 3/8"
OVERALL WIDTH: 23 1/2"
CHAIN GATES AT TOP STEP
RUBBER BUMPER STRIP
MAX CAPACITY IS 350 LBS
TOUGH BAKED IN POWDER
COATED YELLOW FINISH

SPECIAL FEATURES NONE **SALES** 

ENG.

FAB.

**POWER** 

			DIMENSION TOLI	-KANCL I I	/4
	A P P R O V	REPR REQUIR ( COMP AN	UNDERSIGNED, AGRE RESENTED SATISFIES DE REMENTS. I ALSO ACK CONFIRM PRODUCT A PLIANCE WITH ALL APF ID LOCAL REGULATIO ODIFIED UNITS AI [ ] As drawn	ESIGN AND (NOWLEDG) AND INSTAL PLICABLE FE NS AND STA	DIMENSION E MY DUTY TO LATION EDERAL, STATE ANDARDS. RETURNABLE
	<b>A</b>    S	igned:			_Date:
		rinted Na	ame:_ //LL START UPON RECEIP	T OF SIGNED	APPROVAL DRAWING
			THE OTAKE OF ON NEOLII	TOT CICIVED	
FOR INTERNAL USE ONLY		DR'S NAME:			P.O.# X
PROJECT SIGN OFF	\/EC	111 NAA	\ NII IEΔ ←TI IRINI	( )	W O #

4/22/2009

QUOTE #

SCALE: 1:36

FILE NAME:

44-007-365

B. WOOD

QUOTED LEAD TIME: X