

ALTERNATING TREAD STAIR - ATS-5-56-HDG

APPROX WEIGHT: 149.70 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE



TOP STEP - SCALE: 1:12



0

٧

Α

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

STANDARD FEATURES

MODEL NUMBER: ATS-5-56-HDG

CLIMB ANGLE: 56°

NUMBER OF STEPS: 8

(INCLUDING TOP STEP)

TOP STEP HEIGHT: 60"

STEP HEIGHT SPACING: 7 1/2"

HANDRAIL HEIGHT: 18 5/8"

OVERALL HEIGHT: 102 7/16"

OVERALL LENGTH: 49 1/4"

OVERALL WIDTH: 23 1/2"

CHAIN GATES AT TOP STEP

RUBBER BUMPER STRIP

MAX CAPACITY IS 350 LBS

HOT DIPPED GALVANIZED FINISH

HANDRAILS ARE TOUGH BAKED IN POWDER COATED YELLOW FINISH

SPECIAL FEATURES

NONE

DIMENSION TOLERANCE ± 1/4" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE P AND LOCAL REGULATIONS AND STANDARDS. P R

UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE

[] As drawn As marked

Signed: Date:

Printed Name:

	LEAD TIME WILL START UP	PON RECEIP	PT OF SIGNED .	APPROVAL	DRAWING
ISTRIBUTOR'S NAME:				P.O.# X	
VESTIL MANUFACTURING				W.O.# X	
RAV	^{VN BY:} TJH	DATE: 11/	1//2021	SALES: X	
FER	ENCE: X		SCALE: 1:30	FILE NAME:	
UOT	ED LEAD TIME: V	QUOTE #		44-007-7	' 55