ALTERNATING TREAD STAIRS - ATS-6-56-HDG DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ***ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE*** 23 5/8" 9 3/4" TOP STEP - SCALE: 1:12 23 5/8" 20" STEP - SCALE: 1:12 10 1/2" 114 1/4" 18 5/8" 51 1/4" 7 3/16" **STEP HEIGHT SPACING** 71 7/8" 56° TOP STEP HEIGHT

52 3/4"

REFERENCE: X

QUOTED LEAD TIME: X

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

DIMENSION TO FRANCE + 1/4"

SALES: X

44-007-753

SCALE: 1:30 FILE NAME:

STANDARD FEATURES

MODEL NUMBER: ATS-6-56-HDG

9 1/8"

CLIMB ANGLE: 56°

23 1/2"

NUMBER OF STEPS: 10 (INCLUDING TOP STEP)

TOP STEP HEIGHT: 71 7/8" STEP HEIGHT SPACING: 7 3/16"

HANDRAIL HEIGHT: 18 5/8" OVERALL HEIGHT: 114 1/4"

OVERALL LENGTH: 57 1/2" OVERALL WIDTH: 23 1/2"

CHAIN GATES AT TOP STEP

RUBBER BUMPER STRIP MAX CAPACITY IS 350 LBS

HOT DIPPED GALVANIZED FINISH

HANDRAILS ARE TOUGH BAKED IN POWDER

COATED YELLOW FINISH

SPECIAL FEATURES

NONE

	DIMENS	JON TOLLIVATION 1/4
APPROV	COMPLIANCE WITH ALL APPLICAE AND LOCAL REGULATIONS AN	AND DIMENSION LEDGE MY DUTY TO ISTALLATION BLE FEDERAL, STATE ID STANDARDS. L DRAWINGS OR TURNABLE
Α	Signed:	Date:
L	Printed Name:	
	LEAD TIME WILL START UPON RECEIPT OF SIG	GNED APPROVAL DRAWING
DISTR		GNED APPROVAL DRAWING P.O.# X

QUOTE #

11/17/2021