LOW PROFILE PORTABLE PALLET INVERTER - PI-P-3000-3254 APPROX WEIGHT: 1,650 LBS *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON -27"(685)-NOTE: 143/8" (365) THIS PRODUCT WORKS WITH SKIDS, 32-54"(800-1375) NOT CLOSED BOTTOM PALLETS. USE WITH US STANDARD 40" x 48" 6-7/8"(175) 2 1/4"(55) SKIDS ONLY. 35 1/4"(895) 5.7"(144) 35"(889) 6 1/4"(160) 4 3/4" (120) 961/2455) • 70 SPECIFICATIONS: MODEL NUMBER: PI-P-3000-3254 62"(1575) CAPACITY: 3.000 LBS. 45 1/4"(1150) LOWERED HEIGHT: 3 5/8" FORK SIZE: 27" X 35 1/4" 35 1/4"(895) Ø 10x3"(Ø 250×80) FORK OPENING: 32-54" 3.35"(85) 32"(815) Ø3.15x3.35"(Ø80×85) 4x2" 100×50 TURNING RADIUS: 84 1/2" 3/4"(45) OVERALL SIZE: 87 7/16" X 31 1/2" X 89 3/16" 7/8"(22) POWERED PALLET TRUCK POWERED TILT UP / DOWN MANUAL ROTATION 15 3/4"(400) TOUGH BAKED IN POWDER COATED 581/2"(1490) 17" (436) -31 3/4"(804)--**BLACK & YELLOW FINISH** 991/2"(2530) **DIMENSION TOLERANCE ± 1/2"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS 241/2"(625)-36 3/4"(935) REPRESENTED SATISFIES DESIGN AND DIMENSION 18 1/4"(460) Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION Ρ Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS R UNITS REQUIRING APPROVAL DRAWINGS OR 0 R841/2"(R2150) MODIFIED ARE NON-RETURNABLE V [] As marked [] As drawn Α L Date: Signed: Printed Name: TRAVEL SPEED UNLOADED: 2.8 m/h FORK CLAMPING W/O LOAD: 9.5 SEC LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING TRAVEL SPEED LOADED: 2.1 m/h FORK OPENING W/O LOAD: 10 SEC ν. P.O.# χ DRIVE MOTOR: 24V/1.5 KW FORK CLAMING W/ LOAD: 14 SEC VESTIL MANUFACTURING W.O.# LIFT MOTOR: 24V/2.0 KW FORK OPENING W/ LOAD: 7.5 SEC Х FORK TILTING UP W/O LOAD: 15 SEC SALES: X BATTERY: 4-6 VOLT / 200Ah DRAWN BY: DATE: ΤM 06/10/2021

REFERENCE: X

QUOTED LEAD TIME: X

FILE NAME:

PI-P-3000-3254

SCALE: NTS

QUOTE # Х

BATTERY CHARGER: 24V CONTROLLER:2207A-5102 FORK LOWERING DOWN W/O LOAD: 14 SEC FORK TILTING UP W/ LOAD 23 SEC FORK LOWERING DOWN W/ LOAD 13.5 SEC