PORTABLE SCISSOR TABLE - PST-4848-4-47-PTDS APPROX WEIGHT: 1684.69 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ***ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE*** 24V DC POWER UNIT W/ ONBOARD BATTERY CHARGER AND BATTERY **CHARGE INDICATOR** 43" 48 3/8" 36" THROTTLE ASSEMBLY W/ REVERSE SAFETY 12 7/16' 48 3/8" **ELECTRIC TOEGUARDS** (STOPS TABLE FROM LOWERING IF BUMPED) MEETS OSHA 1910.212 54 5/8" ∕⊙ 47" **RAISED** ADJUSTABLE UPWARD TRAVEL LIMIT SWITCH 12" LOWERED

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

Ø8" X 3" PHENOLIC RIGID CASTERS

DIMENSION TOLERANCE ± 1/2" TABLE HEIGHT TOLERANCE ± 1/2" DECK FLATNESS ± 1/4"

STANDARD FEATURES

2 3/4"

MODEL NUMBER: PST-4848-4-47-PTDS

CAPACITY: 4,000 LBS

PLATFORM WIDTH: 48 3/8" PLATFORM LENGTH: 48 3/8"

PLATFORM LOWERED HEIGHT: 12"

PLATFORM RAISED HEIGHT: 47"

OVERALL WIDTH: 48 3/8" OVERALL LENGTH: 81 11/16" GROUND CLEARANCE: 2 3/4"

CASTERS: ONE Ø8" X 3" PHENOLIC SWIVEL

TWO Ø8" X 3" PHENOLIC RIGID

DURABLE LIQUID PAINT BLUE FINISH

SPECIAL FEATURES PST-PTDS

-PTDS OPTIONAL POWER TRACTION DRIVE - 4K TO 5K

 \emptyset 8" X 3" PHENOLIC

SWIVEL CASTER

	[]	[]	
Signed:		Date:	
Printed Nam	е.		

LEAD TIME WILL START UPON RECEIPT OF SIGNED	APPROVAL DRAWIN
STRIBUTOR'S NAME:	P.O.# X

VESTIL MANUFAC	W.O.# X		
DRAWN BY: KGH	DATE: 5/10	0/2018	SALES: X
reference: X		SCALE: 1:18	FILE NAME:
QUOTED LEAD TIME: X	QUOTE #		01-007-392