


DCR-RAR-12



A: Label 232

CAUTION	ATENCIÓN	ATTENTION
DRUM MUST BE IN VERTICAL POSITION WHEN MOVING	EL TAMBOR DEBE DE ESTAR EN LA POSICIÓN VERTICAL CUANDO EN MOVIMIENTO	LE BIDON DOIT ÊTRE EN POSITION VERTICALE LORS D'UN DÉPLACEMENT

VESTIL MANUFACTURING CORPORATION • Phone (260) 665-7586 • Fax (260) 665-1339 • sales@vestil.com • www.vestil.com

D: Label 1153 with 770 overlay

MODEL / MODÉLO / MODÈLE _____
WEIGHT / PESO / MASS _____
CAPACITY / CAPACIDAD / CAPACITÉ _____
SERIAL / SERIE / SÉRIE _____
UNITS: 2.2 lb. = 1kg 1" (or 1in.) = 2.54cm **1153**

B: Label 1049

⚠ WARNING

- Improper use of this fork attachment might result in death or serious injury. **1049**
rev 1220
- Using this front end attachment affects lift truck center of gravity.
 - Before using this fork attachment, US Federal regulation 29 CFR 1910.178 requires you to contact the manufacturer of your lift truck and request:
 - Written approval [29 CFR 1910.178(a)(4)]
 - Markings for (fork) lift truck that:
 - Identify the attachment;
 - Give approximate weight of truck and attachment at maximum elevation with laterally-centered load. [29 CFR 1910.178(a)(5)].
 - DO NOT** use **UNTIL** lift truck is marked with corrected capacity tags.
 - CAPACITY OF TRUCK & ATTACHMENT COMBINATION MIGHT BE LESS THAN CAPACITY OF ATTACHMENT. CONSULT TRUCK CAPACITY TAG/LABEL.**

C: Label 218

⚠ WARNING	⚠ ADVERTENCIAS
Improper use might result in death or serious personal injury. Attach device to fork carriage with safety chain/strap. - Drive lift truck forward until forks contact ends of fork pockets - Chain/straps must not be able to disconnect (slide free) from carriage. - Safety chain/strap must be taut. Connect chain/strap to carriage via shortest line.	El uso impropio puede resultar en muerte o heridas personales. Atar aparato al mástil del montacargas con cadenas/correas. - Maneje el montacargas para adelante hasta que las cuñas hagan contacto con la orilla del bolsillo de las cuñas. - La cadenas y correas no deben de deslizarse (soltarse) del mástil del montacargas. - La cadena/correa de seguridad debe de estar apretado. Asegure la cadena/correa al mástil vía la ruta más corta.

218 rev 0910

E: Label 220

⚠ WARNING	⚠ ADVERTENCIA	⚠ AVERTISSEMENT
KEEP CLEAR WHEN IN USE	MANTENGASE ALEJADO CUANDO SE ESTA OPERANDO	SE TENIR À DISTANCE LORS DU FONCTIONNEMENT

220 Rev 08.03

F: Label 1210

⚠ WARNING

- Using this front end attachment exposes occupants and bystanders to risk of serious personal injuries or death. **1210**
- DO NOT use this front end attachment with rough terrain lift trucks or telehandlers (boom lifts).
 - ONLY use this attachment with high lift fork trucks utilizing a vertical mast and carriage.
 - DO NOT operate truck with attachment on unimproved surfaces. ONLY operate the truck with the attachment on concrete or asphalt surfaces capable of supporting the truck and a full capacity load.

Label 1072 is to be applied to the outside of individual packaging

⚠ WARNING: Reproductive Harm - www.P65Warnings.ca.gov.
⚠ WARNING: Cancer - www.P65Warnings.ca.gov.

⚠ ADVERTENCIA: Daño Reproductivo - www.P65Warnings.ca.gov.
⚠ ADVERTENCIA: Cáncer - www.P65Warnings.ca.gov.

1072

FORK MOUNTED RIGHT ANGLE DRUM ROTATOR

09/28/2023